

EVVOSEMI[®]

THINK CHANGE DO



ESD



TVS



MOS



LDO



Diode



Sensor



DC-DC

Product Specification

▶ Domestic	Part Number	SN74LVC1G00
▶ Overseas	Part Number	SN74LVC1G00
▶ Equivalent	Part Number	SN74LVC1G00

EV is the abbreviation of name EVVO

Product introduction

SN74LVC1G00 is a 2-input NAND integrated circuit, which can realize the mathematical logic operation of $Y=\overline{A+B}$ and $Y=\overline{A*B}$. Advanced CMOS process design is adopted, which has the working characteristics of low power consumption and high output driving capability. The chip can work normally when the power supply voltage VCC is between 1.65V and 5.5V V. And 74LVC1G00 has a variety of small package shapes,It can be widely used in high-end precision instruments, miniaturized low-power handheld devices, artificial intelligence and other fields.


Product features

- Low input current: 0.1uA typical
- Wide working voltage range: 1.65V to 5.5V
- Low static power consumption: 0.1uA typical
- Package form: DBV/DCK/DRL/YZP/ DRY/DSF/ DPW
- High output drive: VCC=4.5V, more than 32MA

product usage

- Portable audio interface
- Blu-ray player and home theater
- digital television
- Solid state drive
- Wireless headphones, smart watches, etc.
- Smart wearable devices

Package form and pin function definition



PIN				DESCRIPTION
NAME	DBV, DCK, DRL, YZP	DRY, DSF	DPW	
A	1	1	2	Input
B	2	2	1	Input
GND	3	3	3	Ground
Y	4	4	4	Output
V _{CC}	5	6	5	Power pin
NC		5		Not connected

Note: NC null pin, no connecting wire inside.

Limit parameter

parameter	symbol	limit value	unit
operating voltage	V_{CC}	6.5	V
input	V_{IN}	-0.5~6.5	V
Output voltage (1)	V_{OUT}	-0.5~6.5	V
Single pin output current	I_{OUT}	25	mA
Or V_{CC} current.	I_{CC}	50	mA
Storage temperature	T_S	-65~150	°C
Pin welding temperature	T_W	260, 10s	°C
Working temperature	T_A	-40~105	°C

Note: 1. In the power-off state of $V_{CC}=0V$, the limit voltage that the output can bear,

2. Limit parameter refers to the limit value that can't be exceeded under any conditions. If it exceeds this limit value, it may cause physical damage such as product deterioration; At the same time, the chip can't work normally when it is close to the limit parameters.

Principle logic diagram



truth table

Inputs		Output
A	B	Y
L	L	H
L	H	H
H	L	H
H	H	L

working conditions

project	symbol	test condition	minimum value	typical value	maximum	unit
operating voltage	VC	—	1.65	—	5.5	V
Input high level voltage	VHI	$VC = 1.65V \sim 1.95V$	$0.65 * VC$	—	—	V
		$VC = 2.3V \sim 2.7V$	1.7V	—	—	
		$VC = 3V \sim 5.5V$	$0.7 * VC$	—	—	
Low-Level Input Voltage	VIL	$VC = 1.65V \sim 1.95V$	—	—	$0.35 * VC$	V
		$VC = 2.3V \sim 2.7V$	—	—	0.7	
		$VC = 3V \sim 5.5V$	—	—	$0.3 * VC$	
input voltage	VI	—	0	—	5.5	V
Output voltage	VO	—	0	—	VC	V
High level output current	IOH	$VC = 1.65V$	—	—	-4	mA
		$VC = 2.3V$	—	—	-8	
		$VC = 3V$	—	—	-16	
		$VC = 4.5V$	—	—	-32	
Low level output current	IOL	$VC = 1.65V$	—	—	4	mA
		$VC = 2.3V$	—	—	8	
		$VC = 3V$	—	—	16	
		$VC = 4.5V$	—	—	32	


Electrical characteristics

 Electrical characteristics of DC: $T=25^{\circ}\text{C}$

project	symbol	test condition	minimum value	typical value	maximum value	unit
High level load voltage	V_{OH}	$I_{OH} = -100\mu\text{A}$	1.65V	1.64	5.5	V
		$I_{OH} = -4\text{ mA}$	1.65V	1.47	—	
		$I_{OH} = -8\text{ mA}$	2.3V	2.15	—	
		$I_{OH} = -16\text{ mA}$	3V	2.73	—	
		$I_{OH} = -32\text{ mA}$	4.5V	4.0	—	
Low level load voltage	V_{OL}	$I_{OH} = 100\mu\text{A}$	1.65V~5.5V	0.01	—	V
		$I_{OH} = 4\text{ mA}$	1.65V	0.11	—	
		$I_{OH} = 8\text{ mA}$	2.3V	0.11	—	
		$I_{OH} = 16\text{ mA}$	3V	0.2	—	
		$I_{OH} = 32\text{ mA}$	4.5V	0.35	—	
incoming current	I_I	A B $V_I = 5.5\text{V}$ 或 GND	0~5.5V	0.01	± 5	μA
				0.01	± 5	
Turn-off current	I_{OFF}	$V_I = 5.5\text{V}$	0	0.01	± 10	μA
		$V_O = 5.5\text{V}$	0	0.01	± 10	
operational current	I_{CC}	$V_I = 5.5\text{V}, I_O = 0$	1.65V~5.5V	0.01	10	μA
		$V_I = \text{GND}, I_O = 0$		0.01	10	
Working current variation value	ΔI_{CC}	$A = V_{CC} - 0.6\text{V}$	3V~5.5V	25	—	μA
		$B = V_{CC}$ 或 GND		25	—	
		$B = V_{CC} - 0.6\text{V}$		25	—	μA
		$A = V_{CC}$ 或 GND		25	—	

 Ac electrical characteristics: $T_a = 25^{\circ}\text{C}$ $V(298) = 5.0\text{V}$, $t_r = \leq 20\text{ns}$. See test method.


project	symbol	test condition	minimum value	typical value	maximum value	unit
Maximum transmission delay time a, B to Y		$C = 15\text{pF}$	—	10	—	ns
		$C = 15\text{pF}$	—	10	—	ns



- Note: 1. CL capacitor is external chip capacitor (0603), which is connected close to the output pin, and the capacitor ground is close to the chip GND;
 2. Input: port input level, $f = 500\text{kHz}$, $D = 50\%$; $t_r = t_f \leq 20\text{ns}$;
 3. Output: Y-terminal output test.

■ Encapsulated information

DBV (SOT23-5)



■ Marking









Diagram of a 5-bit shift register. The register is labeled **CA5**. It has five inputs (A, B, C, D, E) and five outputs (A, B, C, D, E). The inputs are connected to the register, and the outputs are connected to the register.


DRL (SOT-553)




DRY (SOT-886)





DSF (SON-6)




YZP (DSBGA-5)



LAND PATTERN EXAMPLE
SCALE:40X



DPW (X2SON-5)



Ordering information

Order code	Package	Baseqty	Deliverymode
SN74LVC1G00DBVR	SOT23-5	3000	Tape and reel
SN74LVC1G00DCKR	SC70-5	3000	Tape and reel
SN74LVC1G00DSFR	SON-6	5000	Tape and reel
SN74LVC1G00DRYR	SOT-886	5000	Tape and reel
SN74LVC1G00YZPR	DSBGA-5	3000	Tape and reel
SN74LVC1G00DPWR	X2SON-5	3000	Tape and reel
SN74LVC1G00DRLR	SOT-553	4000	Tape and reel

Disclaimer

EVVOSEMI ("EVVO") reserves the right to make corrections, enhancements, improvements, and other changes to its products and services at any time, and to discontinue any product or service without notice.

EVVO warrants the performance of its hardware products to the specifications applicable at the time of sale in accordance with its standard warranty. Testing and other quality control techniques are used as deemed necessary by EVVO to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

Customers should obtain and confirm the latest product information and specifications before final design, purchase, or use. EVVO makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does EVVO assume any liability for application assistance or customer product design. EVVO does not warrant or accept any liability for products that are purchased or used for any unintended or unauthorized application.

EVVO products are not authorized for use as critical components in life support devices or systems without the express written approval of EVVOSEMI.

The EVVO logo and EVVOSEMI are trademarks of EVVOSEMI or its subsidiaries in relevant jurisdictions. EVVO reserves the right to make changes without further notice to any products herein.