

EVVOSEMI[®]

THINK CHANGE DO



ESD



TVS



MOS



LDO



Diode



Sensor



DC-DC

Product Specification

| | | |
|--------------|-------------|---------|
| ▶ Domestic | Part Number | IRF540Z |
| ▶ Overseas | Part Number | IRF540Z |
| ▶ Equivalent | Part Number | IRF540Z |

EV is the abbreviation of name EVVO

- ★ 100% EAS Guaranteed
- ★ Green Device Available
- ★ Super Low Gate Charge
- ★ Excellent CdV/dt effect decline
- ★ Advanced high cell density Trench technology

Product Summary


| BVDSS | R _{DS(on)} | ID |
|-------|---------------------|-----|
| 100V | 22mΩ | 58A |

Description

The IRF540Z is the high cell density trenched N-ch MOSFETs, which provide excellent R_{DS(on)} and gate charge for most of the synchronous buck converter applications.

The IRF540Z meet the RoHS and Green Product requirement, 100% EAS guaranteed with full function reliability approved.

TO220 Pin Configuration



Absolute Maximum Ratings

| Symbol | Parameter | Rating | Units |
|---------------------------------------|--|------------|-------|
| V _{DS} | Drain-Source Voltage | 100 | V |
| V _{GS} | Gate-Source Voltage | ±20 | V |
| I _D @T _C =25°C | Continuous Drain Current, V _{GS} @ 10V ¹ | 58 | A |
| I _D @T _C =100°C | Continuous Drain Current, V _{GS} @ 10V ¹ | 37 | A |
| I _{DM} | Pulsed Drain Current ² | 130 | A |
| EAS | Single Pulse Avalanche Energy ³ | 84 | mJ |
| I _{AS} | Avalanche Current | 41 | A |
| P _D @T _C =25°C | Total Power Dissipation ⁴ | 149 | W |
| T _{STG} | Storage Temperature Range | -55 to 150 | °C |
| T _J | Operating Junction Temperature Range | -55 to 150 | °C |

Thermal Data

| Symbol | Parameter | Typ. | Max. | Unit |
|------------------|--|------|------|------|
| R _{θJA} | Thermal Resistance Junction-Ambient ¹ | --- | 62 | °C/W |
| R _{θJC} | Thermal Resistance Junction-Case ¹ | --- | 0.84 | °C/W |

Electrical Characteristics ($T_J=25^\circ\text{C}$, unless otherwise noted)

| Symbol | Parameter | Conditions | Min. | Typ. | Max. | Unit |
|--------------|--|--|------|------|-----------|------------|
| BV_{DSS} | Drain-Source Breakdown Voltage | $V_{GS}=0V$, $I_D=250\mu A$ | 100 | --- | --- | V |
| $R_{DS(ON)}$ | Static Drain-Source On-Resistance ² | $V_{GS}=10V$, $I_D=30A$ | --- | --- | 22 | m Ω |
| $V_{GS(th)}$ | Gate Threshold Voltage | $V_{GS}=V_{DS}$, $I_D=250\mu A$ | 2.5 | --- | 4.5 | V |
| I_{DSS} | Drain-Source Leakage Current | $V_{DS}=80V$, $V_{GS}=0V$, $T_J=25^\circ\text{C}$ | --- | --- | 1 | μA |
| | | $V_{DS}=80V$, $V_{GS}=0V$, $T_J=55^\circ\text{C}$ | --- | --- | 5 | |
| I_{GSS} | Gate-Source Leakage Current | $V_{GS}=\pm 20V$, $V_{DS}=0V$ | --- | --- | ± 100 | nA |
| g_{fs} | Forward Transconductance | $V_{DS}=5V$, $I_D=30A$ | --- | 31 | --- | S |
| R_g | Gate Resistance | $V_{DS}=0V$, $V_{GS}=0V$, $f=1\text{MHz}$ | --- | 1.9 | 3.8 | Ω |
| Q_g | Total Gate Charge (10V) | $V_{DS}=80V$, $V_{GS}=10V$, $I_D=30A$ | --- | 27.6 | --- | nC |
| Q_{gs} | Gate-Source Charge | | --- | 11.4 | --- | |
| Q_{gd} | Gate-Drain Charge | | --- | 7.9 | --- | |
| $T_{d(on)}$ | Turn-On Delay Time | $V_{DD}=50V$, $V_{GS}=10V$, $R_G=3.3\Omega$, $I_D=30A$ | --- | 16.5 | --- | ns |
| T_r | Rise Time | | --- | 35 | --- | |
| $T_{d(off)}$ | Turn-Off Delay Time | | --- | 17.5 | --- | |
| T_f | Fall Time | | --- | 12 | --- | |
| C_{iss} | Input Capacitance | $V_{DS}=15V$, $V_{GS}=0V$, $f=1\text{MHz}$ | --- | 1890 | --- | pF |
| C_{oss} | Output Capacitance | | --- | 268 | --- | |
| C_{rss} | Reverse Transfer Capacitance | | --- | 67 | --- | |

Diode Characteristics

| Symbol | Parameter | Conditions | Min. | Typ. | Max. | Unit |
|----------|--|---|------|------|------|------|
| I_S | Continuous Source Current ^{1,5} | $V_G=V_D=0V$, Force Current | --- | --- | 58 | A |
| I_{SM} | Pulsed Source Current ^{2,5} | | --- | --- | 130 | A |
| V_{SD} | Diode Forward Voltage ² | $V_{GS}=0V$, $I_S=1A$, $T_J=25^\circ\text{C}$ | --- | --- | 1.2 | V |
| t_{rr} | Reverse Recovery Time | $I_F=30A$, $dI/dt=100A/\mu s$, $T_J=25^\circ\text{C}$ | --- | 22 | --- | nS |
| Q_{rr} | Reverse Recovery Charge | | --- | 20 | --- | nC |

Note :

1. The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper.
2. The data tested by pulsed, pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$
3. The EAS data shows Max. rating. The test condition is $V_{DS}=25V$, $V_{GS}=10V$, $L=0.1mH$, $I_{AS}=41A$
4. The power dissipation is limited by 150°C junction temperature
5. The data is theoretically the same as I_D and I_{DM} , in real applications, should be limited by total power dissipation.

Typical Characteristics




Fig.1 Typical Output Characteristics




Fig.3 Forward Characteristics of Reverse




Fig.5 Normalized $V_{GS(th)}$ vs. T_J




Fig.2 On-Resistance v.s Gate-Source




Fig.4 Gate-Charge Characteristics




Fig.6 Normalized $R_{DS(on)}$ vs. T_J




Fig.7 Capacitance




Fig.8 Safe Operating Area




Fig.9 Normalized Maximum Transient Thermal Impedance




Fig.10 Switching Time Waveform




Fig.11 Unclamped Inductive Switching Waveform

Disclaimer

EVVOSEMI ("EVVO") reserves the right to make corrections, enhancements, improvements, and other changes to its products and services at any time, and to discontinue any product or service without notice.

EVVO warrants the performance of its hardware products to the specifications applicable at the time of sale in accordance with its standard warranty. Testing and other quality control techniques are used as deemed necessary by EVVO to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

Customers should obtain and confirm the latest product information and specifications before final design, purchase, or use. EVVO makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does EVVO assume any liability for application assistance or customer product design. EVVO does not warrant or accept any liability for products that are purchased or used for any unintended or unauthorized application.

EVVO products are not authorized for use as critical components in life support devices or systems without the express written approval of EVVOSEMI.

The EVVO logo and EVVOSEMI are trademarks of EVVOSEMI or its subsidiaries in relevant jurisdictions. EVVO reserves the right to make changes without further notice to any products herein.